



# BioMop Plus

| Contains Bacillus microbial blend

## Floor- and Drain-safe Grease and Organic Waste Remover

Specially designed for cleaning restaurant and commercial kitchen floors and drains, BioMop Plus™ combines an advanced formula for floor cleaning and a proprietary microbial blend of concentrated live bacterial cultures for degrading the most resistant grease molecules — long-chain fatty acids. This biodegradable, noncaustic, and nonhazardous solution is a safe and effective choice in restaurants and food service facilities. Unlike mopping or power washing with standard soap-based and chemical floor-cleaning products, which do not remove grease and organic waste, the powerful microbial formula in BioMop Plus™ digests the organic waste and breaks down complex grease molecules to help reduce foul odors.

### FEATURING

- ✓ Mode of action: Emulsifiers, builders, stabilized enzymes, and naturally-occurring viable bacterial cultures
- ✓ Over 200 billion CFU (colony forming units) of bacilli per gallon
- ✓ 2+ years stability at 33°F to 120°F

SCAN TO LEARN MORE



## Application Sites

Safe for mopping and hosing all washable surfaces in restaurants, food service, and food-processing facilities. Use on floors, grout, drain lines, and hard-to-access areas. Safe for all plumbing and septic systems.

## Effective Against

Grease and organic waste, foul odors, and clogged slow drains.

ITEM NO.	UNIT SIZE	CASE SIZE
14760	1 gal. bottle	4 x 1 gal. bottle
14761	5 gal. pail	1 x 5 gal. pail

Nonfood Compounds  
Category Code - A4  
Registration - 140642



Contact your authorized AMGUARD Environmental Technologies distributor or visit [amguardtech.com/product/biomop-plus](http://amguardtech.com/product/biomop-plus)

**AMGUARD**  
ENVIRONMENTAL TECHNOLOGIES



# BioMop Plus

| Contains Bacillus microbial blend

## FOR MOPPING APPLICATIONS

1. Add 4 ounces of BioMop Plus™ to 2 gallons of water.
2. Mop floor in normal manner, being sure to mop in all corners, cracks, and crevices and under equipment.
3. After mopping is completed, pour remaining mop water into each drain in equal portions.
4. If problem areas exist that cannot be reached by mopping, pour undiluted BioMop Plus™ into a spray bottle and spray problem areas until wet.

## FOR HOSING AND POWER-WASHING APPLICATIONS

1. Pre-rinse floor with hose or power washer in the usual manner with only water.
2. Using either the BioMop Plus™ Hose End Sprayer (for smaller facilities) or the BioMop Plus™ Application System (for larger facilities), apply BioMop Plus™ according to the application system's instructions.
3. Thoroughly rinse all floor areas with BioMop Plus™ including under equipment, in cracks and crevices, and around all drain areas.
4. If necessary, squeegee excess water into floor drains.

## FOR FOAMING APPLICATIONS

Mix 6 oz. BioMop Plus™, 3 oz. foaming agent, and 23 oz. water in a standard quart foamer. Foam into cracks and crevices, underneath equipment, and into hard-to-reach areas.



BioMop Plus is not subject to registration under FIFRA.

©2023 AMVAC Chemical Corporation. All rights reserved. AMERICAN VANGUARD, AMVAC, AMGUARD, BIOMOP PLUS and respective logos are trademarks owned by AMVAC Chemical Corporation. AMGUARD Environmental Technologies is the specialty markets division of AMVAC Chemical Corporation, a wholly owned subsidiary of American Vanguard Corporation. AMGUARDECH.com AET-23018

**AMGUARD**<sup>™</sup>  
ENVIRONMENTAL TECHNOLOGIES